

CLA-ALBUS



PAPERS

you can trust

TECHNICAL SPECIFICATION

Property	Reference Standard	Units	Nominal Value						
Basis Weight	ISO 536	g/m ²	160	180	210	240	315	430	
Taber Stiffness	MD	ISO 2493	mN.m	1.8	2.3	4.0	5.0	8.0	--
	CD			0.9	1.2	2.0	2.5	4.0	--
Thickness	ISO 534	μm	190	210	240	280	350	500	
Bekk Smoothness	ISO 5627	s	27	23	23	23	23	23	
Moisture Content	ISO 287	%	7.5	7.5	7.5	7.5	7.5	7.5	
CIE Whiteness	ISO 11475	%	144.0	144.0	144.0	144.0	144.0	144.0	

MD-Machine Direction; CD-Cross-Machine Direction

PRODUCT SPECIFICATION

Basis Weight (g/m ²)	Size (cm)	Packets per pallet	Reams per pallet	Sheets per pack	Finish
160	50x65	92	23		Glazed
	61x86	46	11,5	125	
	100x65	46	11,5		
	70x100	46	11,5		
180	50x65	80	20		
	61x86	40	10	125	
	100x65	40	10		
210	70x100	40	10		
	50x65	64	16	125	
	50x65	60	15		
240	61x86	30	7,5		
	100x65	30	7,5	125	
	70x100	30	7,5		
315	50x65	48	12		
	61x86	24	6		
	100x65	24	6	125	
430	70x100	24	6		
	50x65	32	8	125	

Product certifications available



EU Ecolabel: PT/011/003



www.papeldoprado.com

This information is subject to change without notice.
Last update: 07/2024